Installation: IP500 V2 Installation > Starting the System



Checking the LEDs

Control Unit LEDs

LED	Description
Optional SD System SD	 Off = <u>Card shutdown</u>. Green on = Card present. Green flashing = Card in use. Orange steady = Reset imminent. Red flashing = Card initializing or shutting down. Red fast flashing = card full Red steady = Card failure/wrong type.
СРИ	 Alternate red/green = Starting up. Green on = Okay. Red on = No software. Flashing Red = Error/Shutdown.

Base Card LEDs

Base Card	LEDs 1 to 8 Usage				
All Cards	LED1 is also used for base card status:				
	· Red On · Red Slo	= Error w Flash = Initializing	 Red Flash every 5 seconds okay. Red Fast Flash = System shut 		
IP500 Analog Phone	No status LEDs are used for analog phone extensions.				
IP500 Digital Station	• Green On = Phone detected.				
IP500 Combination	LEDs 1 to 6 • Green On = Phone detected.				
IP500 VCM	 LEDs 1 to 8 are unlabelled. They are used to indicate voice compression channel usage. Each LED lit represents 12.5% of the available voice compression channel capacity in use (total card capacity rather than licensed capacity). 				
IP500 4-Port Expansion	LEDs 1 to 8 are used for the expansion ports on the rear of the control unit. LEDs 9 to 12 are used for the card's own expansion ports.				
	Green	On	Expansion module present.		
	Red	Flashing	Initializing.		
	Red	On	Error.		
	Orange	Regular Flash	Base card okay.		

Trunk Daughter Card LEDs

Trunk Daughter Card	LEDs 9 to 12 Usage			
All cards	LED 9 is also used for daughter card status.			
	Red On = ErrorRed Slow Flash = Initializing.	 Red Flash every 5 seconds = Card okay. Red Fast Flash = System shutdown. 		
Analog Trunk	 Green on = Card fitted. Green flashing = Trunk in use.			
PRI Trunk	 Off = No trunk present. Green on = Trunk present. Green flashing = Trunk in use. Red/Green Fast Flash (port 9) or Green Fast Flash (port 10) = Alarm indication signal (AIS) from the trunk remote end. 			

- · **Green on** = Trunk present.
- Green flashing = Trunk in use.

External Expansion Module LEDs

- · Green on = Module okay.
- Red flashing = Module starting up/Loading firmware.
- Green flashing = Module starting up/Loading firmware (IP500 DS16A/30A module).
- Red on = Error.

© 2011 AVAYA 15-601042 Issue 24.i.-13:00, 20 December 2011 (checking_the_leds.htm)

Performance figures, data and operation quoted in this document are typical and must be specifically confirmed in writing by Avaya before they become applicable to any particular order or contract. The company reserves the right to make alterations or amendments at its own discretion. The publication of information in this document does not imply freedom from patent or any other protective rights of Avaya or others.

All trademarks identified by (R) or TM are registered trademarks or trademarks respectively of Avaya Inc. All other trademarks are the property of their respective owners.

 $http://marketing tools.avay a.com/knowledge base/business partner/ip of fice/merged \textit{Projects/installation/checking_the_leds.htm?} \\ zoom_highlight=leds.htm?$

Last Modified: 26/09/2011